

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 March 2003 (20.03.2003)


PCT

(10) International Publication Number
WO 03/023185 A1

- (51) International Patent Classification⁷: **E21B 43/08**, 34/10, 43/12
- (21) International Application Number: PCT/EP02/10052
- (22) International Filing Date:
4 September 2002 (04.09.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
01203387.4 7 September 2001 (07.09.2001) EP
- (71) Applicant (*for all designated States except CA, US*): **SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.** [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **SMITH, David, Randolph** [US/US]; 1121 Mission Hills, College Station, TX 77845 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: ADJUSTABLE WELL SCREEN ASSEMBLY



(57) Abstract: An adjustable well screen assembly comprises a sandscreen (5) which is wrapped around a perforated base pipe (3) and a perforated sleeve (1) which is movably disposed concentrically inside the base pipe (3) between a first, closed, and open, position. In said first position of the sleeve (1) the perforations of the sleeve and base pipe (3) are unaligned and hydraulically isolated from each other and flow of fluids from the outer diameter of the screen (5) into the interior of the sleeve (1) is inhibited. In said second position the perforations of the sleeve and the base pipe are aligned and connected in fluid communication with each other and fluids are permitted to flow from the formation through the sandscreen and the perforations of the sleeve and base pipe into the interior of the sleeve.

WO 03/023185 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

ADJUSTABLE WELL SCREEN ASSEMBLY

FIELD OF INVENTION

This invention relates to an adjustable well screen assembly for controlled inflow of fluids from a hydrocarbon fluid containing formation into the production tubing of a hydrocarbon fluid production well. The invention also relates to a hydrocarbon fluid production well, which is equipped with one or more adjustable well screen assemblies.

BACKGROUND OF INVENTION

The art of completing wells to exclude solids particles produced by well fluids is commonly known in the literature as gravel packing.

It is common practice in the construction of wells bored into the earth to dispose steel casing or other tubular conduits inside of the well. In some well constructions the casing is grouted into the bore by placing portland cement in the annular space between the casing and the well bore. The casing can be deployed through the depth where the productive subterranean formation or plurality of formations is encountered below the surface. In the former the well completion is referred to those familiar with the art of well completions as open hole completions, whereas those well completions where the casing and cement is run through or past the depth of the productive formation is known to those familiar with the art of well completions as cased holes. In either case of open hole completions or cased hole completions it is well practised art to dispose across the production formation depths sand screens,

slotted pipes, or pipes with holes pre-perforated at surface into the well casing on a second continuous tube known in the literature as production tubing.

5 Production tubing is disposed inside of the casing extending from the surface to a depth closer to the production formation. It is often desirable to place a packer on the end of the production tubing to force well fluids up the tubing and avoid fluids being produced up the casing. The production tubing is then a removable
10 pipe that is disposed in wells generally in jointed lengths of 40 feet (about 12 m), but can be deployed as a continuous tubing string in what is commonly known in the oil and gas industry as continuous tubing. It is common practice to deploy in production tubing string various
15 apparatus to allow for well fluid control. It is also common to control such devices from surface using electrical and hydraulic tubes disposed simultaneously with the production tubing and connected to the outer diameter of the production tubing. These hydraulic tubes
20 are known to those familiars with the art of well completions as control lines.

In the cased hole completions it is common practice to run explosive charges into the well after the casing is cemented across the productive formation depths and
25 perforate holes through the casing and cement into the productive formation to create a path for fluid flow into the well.

In many wells either in cased or open hole completions unwanted formation solids are produced into
30 the well along with the production fluids. These solids are often undesirable and many methods of stopping these solids from flowing into the well whilst producing the fluids are well defined in the literature as the art sand

control. One of the more familiar methods of stopping solid flow is to perform a gravel pack.

5 A gravel pack is performed by placing a known size of sand, which is referred to as the gravel, into the well across the production formation to create a filter medium to stop or reduce the flow of solid materials from the formation into the well. The gravel is most commonly prohibited from flowing into the well by a device commonly know as a well screen. The well screens are
10 designed to keep the specialized sand mesh, known as the gravel, in place in the annular space between the casing or well bore outside of the screens forming the filter media.

The current methods of placing a gravel pack is
15 requires that the screens be deployed in the well on a tubing string from surface until the screens are at the depth of the producing formation. At this point sand is placed around the screens by various methods of pumping, circulating, and other wise dispose sand around the
20 screens. Once the sand is placed around the screens the tubing string is detached from the screens and extracted from the well. Thereafter the production tubing with packers, control lines, sliding sleeves, and packers are disposed in the well above the screens. Hence the screens
25 are detached from the production string in the common known methods of the industry.

It is current practice to build the well screens out of wire wrap welded to bars running parallel to the screen axis and said bars are placed around a pipe
30 extending the length of the screen with holes through the pipe. This pipe is commonly known to those familiars with the art as the base pipe and forms the structure to which the wire wrap and welded bars are attached. Hence the

commonly known well screen consists of wire wrap helically wrapped around the circumference of the screen attached to welded bars that are fitted onto the outer diameter of base pipe. In other designs of sand screens the screen is manufactured with sintered materials located between the wire wrap or in some cases outside of the wire wrap. In all cases the screen has an inner pipe base that holes or other geometric penetrations to allow fluids to flow into the screens inner diameter.

The well screen lengths disposed in wells vary in length to accommodate the depth and heights of production zones. To accommodate deployment of screens they are run in sections and connected on surface to match the height of the production zones.

In many wells there exists in one common well bore multiple production formations that are perforated or otherwise left open hole to allow simultaneous production from several formations at varying depths into the well bore and up the production casing. Often in these multiple production formations wells the different formations in the earth are separated by lithology that does not have productive fluids often times due to lower permeability and porosity. With the current art these varying production formations are completed simultaneously and flow into a common production tubing to surface. It often occurs that one productive formation will produce less fluids, or unwanted fluids, or for resource management reasons the varying formations may be more desirably produced at different flow rates or be produced at different times. In the case of gravel packed wells the methods to shut of production from a formation in a well with multiple production formations producing simultaneously into a common well bore requires

mechanical well intervention techniques none to those familiar to the art. These intervention techniques can include, squeeze cementing, the setting of plugs via wireline and rig methods, and the pulling of production tubing, control lines, electrical cable, packers, sleeves and other disposed subterranean devices in the well. The above prior art techniques require mechanical intervention into the well with pipes, wireline, or pumped chemicals into the well bore to affect the inflow of fluids into and through screen systems.

US patent No. 5,447,201 discloses an adjustable fluid inflow assembly for an oil or gas well where the influx of fluids from a plurality of annular inflow zones is controlled by a series of annular disk shaped valves which are each arranged between a downstream end of each inflow zone and a production tubing passing therethrough.

A disadvantage of the known assembly is that all fluid entering an annular inflow zone needs to be discharged through an annular disk shaped valve and the fluid flow rate in each valve is therefore high which causes a high rate of wear of the valve. The current invention aims to alleviate this and other disadvantages of the known well inflow control assembly such that production formations can be shut off or their fluid production reduced from production zones by non-intervention methods from surface.

SUMMARY OF THE INVENTION

The adjustable well screen assembly according to the invention thereto comprises a sandscreen which is arranged around a perforated base pipe and a perforated sleeve which is arranged concentrically relative to the base pipe and is movable relative to the base pipe between a first and a second position. In said first

position of the sleeve the perforations of the sleeve and base pipe are hydraulically isolated from each other and flow of fluids from the outer diameter of the screen into the interior of the sleeve is inhibited. In said second position the perforations of the sleeve and the base pipe are connected in fluid communication with each other and fluids are permitted to flow from the formation through the sandscreen and the perforations of the sleeve and base pipe into the interior of the sleeve.

Preferably, the sleeve is arranged within the base pipe and the outer diameter of the sleeve is slightly smaller than the inner diameter of the base pipe and the sleeve is connected to an actuator, such as a hydraulic or electrical motor, which is designed to rotate and /or axially translate the sleeve within the base pipe.

Optionally, the actuator is designed to rotate and/or translate the sleeve such that the sleeve is positionable in a range of intermediate positions between the first and second position, in which intermediate positions the perforations of the sleeve and base pipe form adjustable flow restrictions which can be gradually opened and closed.

The sandscreen may be equipped with one or more sensors for monitoring physical parameters such as the pressure, temperature, velocity and/or composition of the fluids flowing through the screen and the actuator is designed to move the sleeve between the first and second position thereof in response to signals generated by at least one of the sensors deployed in the screen system.

The invention also relates to a hydrocarbon fluid production well comprising a hydrocarbon fluid inflow zone which is equipped with a plurality of axially spaced adjustable well screen assemblies with perforated base

pipes in which perforated sleeves are movably arranged wherein the perforated base pipes of adjacent adjustable well screen assemblies are interconnected by blank pipe sections on which an expandable packers is arranged which provides a fluid seal in the annular space between the outer surface of the blank pipe section and the inner surface of the wellbore.

In such case it is preferred that the sleeve of each adjustable well screen assembly is movable between the first and second position independently of position of the other sleeve or sleeves.

The present invention teaches an improved method of disposing well screens in to wells such that production formations fluid flows into the well can be controlled by subterranean devices disposed in the well attached to well screen systems of this invention.

Thus the present invention provides an apparatus to allow for well screen system to be disposed into well bores simultaneously with production tubing, and control tubes deployed continuously from surface to the sand screen system depths. Hence this invention teaches the use of continuous connection of tubes and or electrical cable from the surface to the production formations depths where the tubes are attached to sand screen systems prior to, during, and after the gravel pack operations such the tubes and screen system do not need to be disconnected from the surface deployed production tubing. One end of the control tube extends to surface to allow communication and power to be communicated to the subterranean depth where the sand screen system is disposed.

This invention apparatus then allows subterranean devices and sensors to be attached to sand screen systems

such that data can be read and signals and power can be sent to the down hole system.

This invention allows for sand screen systems to reduce or shut off fluid flow, determine the flow characteristics and reservoir properties of down hole formations, and to isolate different production zones completed simultaneously in a common well bore.

DESCRIPTION OF A PREFERRED EMBODIMENT

Fig. 1 depicts a longitudinal sectional view of an adjustable well screen assembly according to the invention;

Fig. 2 depicts a schematic side view of an inflow zone of an oil and/or gas production well in which three adjustable well screen assemblies according to the present invention are arranged;

Fig. 3 depicts in more detail the upper end of one of the movable sleeves of Fig.1 and 2 and the actuator mechanism for axially translating the sleeve within the base pipe; and

Fig. 4 depicts a schematic three dimensional view of an alternative arrangement of a well screen and perforated base pipe and sleeve assembly according to the invention.

The adjustable screen assembly shown in Fig. 1 comprises an inner sleeve 1 having perforations 2 being disposed concentrically inside of a well screen's 5 inner diameter base pipe 3 having perforations 4 to allow fluid to flow from the sand screen 5 into the interior 7 of the inner sleeve 1. The inner sleeve 1 is axially slidable within the base pipe 3 such that appropriate sealing rings 6 can be moved between the second position shown in Fig. 1, in which well fluids are permitted to flow through the sandscreen 5 and the aligned perforations 4

and 2 of the base pipe 3 and inner sleeve 1 into the interior of the sleeve 1 and a first position (not shown) in which the sealing rings 6 close off the perforations 4 in the base pipe 3 such that the fluid flow from the sandscreen 5 into the interior of the sleeve 1 is inhibited or stopped. This axial movement of the inner sleeve 1 relative to the base pipe 3 may be initiated by a hydraulic piston and cylinder assembly 8,9 which is shown in Fig. 3. The hydraulic piston and cylinder assembly 8,9 may be connected to a hydraulic pump (not shown) at the earth surface by a hydraulic conduit 10.

The adjustable well screen assembly according to the invention may comprise any suitable combination of electrical power, hydraulic power, or optic powered apparatus that allow communication of power to, and transmission of data from, the assembly. In the embodiment shown in Fig. 3 the inner sleeve 1 is actuated from surface with hydraulic pressure supplied from surface through the hydraulic conduit 10. In this embodiment the hydraulic pressure would force the hydraulic piston 8 and associated perforated inner sleeve 1 to a new position in the perforated base pipe 3 changing the rate of flow through the well screen 5. Pressure, temperature, velocity, composition and/or other sensors 11 may be deployed in or around the sandscreen 5 to indicate the flow, fluid, and pressure changes resulting from the varying sleeve position and said sensors 11 transmit data to surface via one or more fibre optical and/or electrical signal transmission conduits 12 attached to the screen 5. It is also clear to any familiar to the art that said communication and power to the screen can be achieved by electrical optical, electromagnetic and or acoustic power and signal

transmission methods. Hence the invention teaches the use of multiple power and communication methods to be used in the invention for both communication with the inventions sensors, and to power the subterranean devices of the invention.

Fig. 2 illustrates an embodiment of the invention comprising three adjustable screen assemblies 20A, 20B and 20C each with their own inner inner sleeve 1A, 1B and 1C connected to surface via simultaneously disposed power and signal transmission conduits 10 and 12. Hence this invention teaches the simultaneous disposal and use of multiple adjustable sand screen assemblies 20 A, B and C such that one screen 20C can be opened whilst another 20A is substantially closed whilst another 20B is partly moved to reduce flow. It is clear to those familiar to the art of well production that said invention can be used to change inflow of several completed production formations without the current industry practice of well intervention.

In the embodiment shown in Fig. 2 a pair of packers 21 is arranged around blank sections of the production tubing 23 between the wire wraps 5A, 5B and 5C of three adjustable well screen assemblies 20A, 20B and 20C which are each similar to the well screen assembly shown in Fig. 1. These packers 21 form seals in the annular space between the inner surface of the well casing 22 and the production tubing 23 which carries the adjustable sand screen assemblies 20A, 20B and 20C. The packers 21 are connected to the production tubing 23. The packers 21 are inflated or set once the production tubing is at the proper depth in the well 25 adjacent to perforations 26 that have been shot through the well casing 22 and surrounding cement lining 28 into an oil

and/or gas bearing formation 27 surrounding the well 25. Once the packers 21 and screen assemblies 20A-C are at the proper depth the packers 21 are set from surface using the various methods known to those familiar with the art such as hydraulic, electrical, and optical methods. Hence this invention teaches the simultaneous disposal via the production tubing 23 of adjustable sandscreen assemblies 20A-C and packers 21 attached thereto.

An additional embodiment of this invention (not shown) teaches the simultaneous production-tubing disposal of additional tubes and subterranean devices with the screen system on the production tubing. These devices can include down hole safety valves, down hole chokes, down hole valves and other devices discussed in the literature such that said devices are disposed simultaneously with the well screen system deployed on the production tubing.

Fig. 4 shows yet another embodiment of an adjustable well screen assembly according to the invention. In the embodiment shown in Fig. 4 a perforated inner sleeve 40 is rotatably arranged within a perforated base pipe 41 such that the perforations are unaligned in one position of the sleeve and become aligned when the sleeve is rotated within the base pipe 41. The inner sleeve 40 closely fits within the base pipe 41 and the contact surfaces may be equipped with a low friction coating to reduce the torque required to rotate the sleeve 40 relative to the base pipe. The patterns of the perforations 42 in the sleeve 40 and base pipe 41 may be slightly offset so that when the sleeve 40 is in its second position the perforations at the downstream end of the screen assembly are already slightly offset and that

when the sleeve 40 is rotated towards its first position the perforations at the downstream end are closed off earlier than the perforations 42 at the upstream end of the adjustable well screen. The perforations 42 may be
5 circular or have another shape to modify the level of fluid influx into the interior of the sleeve 40 between the upstream and downstream ends of the sleeve 40 as a result of incremental rotation of the sleeve from its first, closed, position towards its second, open,
10 position and vice versa.

C L A I M S

1. An adjustable well screen assembly comprising a sandscreen which is arranged around a perforated base pipe and a perforated sleeve which is movably disposed concentrically relative to the base pipe between a first
5 and a second position, wherein in said first position of the sleeve the perforations of the sleeve and base pipe hydraulically isolated from each other and flow of fluids from the outer diameter of the screen into the interior of the sleeve is inhibited and in said second position
10 the perforations of the sleeve and the base pipe are connected in fluid communication with each other and fluids are permitted to flow from the formation through the sandscreen and the perforations of the sleeve and base pipe into the interior of the sleeve.

15 2. The well screen assembly of claim 1, wherein the outer diameter of the sleeve is slightly smaller than the inner diameter of the base pipe and the sleeve is connected to an actuator, which is designed to rotate and/or axially translate the sleeve within the base pipe.

20 3. The well screen assembly of claim 2, wherein the actuator is designed to rotate and/or translate the sleeve such that the sleeve is positionable in a range of intermediate positions between the first and second position, in which intermediate positions the
25 perforations of the sleeve and base pipe are partially aligned and form adjustable flow restrictions.

4. The well screen assembly of claim 2, wherein the sandscreen is equipped with one or more sensors for monitoring physical parameters such as the velocity

and/or composition of the fluids flowing through the screen and the actuator is designed to move the sleeve between the first and second position thereof in response to signals generated by at least one of the sensors
5 deployed in the screen system.

5. The well screen assembly of claim 2, wherein the actuator is a hydraulic or electrical motor.

6. The well screen assembly of claim 2, wherein the sleeve is rotatably arranged within the base pipe.

10 7. A hydrocarbon fluid production well comprising a hydrocarbon fluid inflow zone which is equipped with a plurality of axially spaced adjustable well screen assemblies according to any one of claims 1 to 6, wherein the perforated base pipes of adjacent adjustable well
15 screen assemblies are interconnected by blank pipe sections on which an expandable packer is arranged which provides a fluid seal in the annular space between the outer surface of the blank pipe section and the inner surface of the wellbore.

20 8. The hydrocarbon fluid production well of claim 7, wherein the sleeve of each adjustable well screen assembly is movable between the first and second position independently of position of the other sleeve or sleeves.

1/1

Fig.1.




Fig.4.




Fig.3.





Fig.2.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 02/10052

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E21B43/08 E21B34/10 E21B43/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 112 815 A (CARLSEN HANS-PAUL ET AL) 5 September 2000 (2000-09-05) column 3, line 33-44 column 4, line 36-43 column 4, line 65 -column 5, line 32; figure 6	1-3,5,6
Y	column 5, line 61,62	4,7,8
X	FR 2 543 213 A (TURKMENSK NI GEOLOGORASVEDOC) 28 September 1984 (1984-09-28) page 7, line 30 -page 8, line 14; figures 1,3	1,2
X	US 6 220 357 B1 (CARMICHAEL MARK ET AL) 24 April 2001 (2001-04-24) figures 1,5	1,2,6
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

2 December 2002

Date of mailing of the international search report

09/12/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

van Berlo, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 02/10052

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	GB 2 325 949 A (BAKER HUGHES INC) 9 December 1998 (1998-12-09) page 10, line 4 -page 12, line 20; figures 1-7 page 14, line 16 -page 16, line 6 ----	4,7,8
X	US 3 993 130 A (PAPP JOHN C) 23 November 1976 (1976-11-23) figures 1-4 ----	1,6
X	US 4 691 778 A (PYNE R DAVID G) 8 September 1987 (1987-09-08) figures 2-5 ----	1
A	US 5 111 883 A (SAVERY WINSOR) 12 May 1992 (1992-05-12) column 4, line 35 -column 5, line 3; figures 2-4 ----	1
A	WO 01 29368 A (SCHLUMBERGER TECHNOLOGY CORP) 26 April 2001 (2001-04-26) page 7, line 24 -page 8, line 4 page 9, line 19-23; figures 1-8 ----	4
P,A	GB 2 369 382 A (SCHLUMBERGER HOLDINGS) 29 May 2002 (2002-05-29) figures 2,4 ----	4
P,A	WO 02 06593 A (HALLIBURTON ENERGY SERV INC ;RESTARICK HENRY L (US); ROBISON CLARK) 24 January 2002 (2002-01-24) the whole document -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 02/10052

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6112815	A	05-09-2000	AU 716036 B2 AU 7509796 A BR 9611586 A CA 2236264 A1 DE 69607853 D1 EP 0858548 A1 NO 981931 A WO 9716623 A1	17-02-2000 22-05-1997 06-04-1999 09-05-1997 25-05-2000 19-08-1998 29-04-1998 09-05-1997
FR 2543213	A	28-09-1984	DE 3309031 A1 AU 554092 B2 AU 1268683 A FR 2543213 A1	20-09-1984 07-08-1986 27-09-1984 28-09-1984
US 6220357	B1	24-04-2001	GB 2327445 A , B	27-01-1999
GB 2325949	A	09-12-1998	AU 713643 B2 AU 6474698 A CA 2236944 A1 NO 982054 A US 6112817 A US 6023443 A	09-12-1999 12-11-1998 06-11-1998 09-11-1998 05-09-2000 08-02-2000
US 3993130	A	23-11-1976	NONE	
US 4691778	A	08-09-1987	NONE	
US 5111883	A	12-05-1992	WO 9309887 A1 EP 0613406 A1 RU 2098334 C1	27-05-1993 07-09-1994 10-12-1997
WO 0129368	A	26-04-2001	US 6343651 B1 AU 7880000 A GB 2372527 A NO 20021798 A WO 0129368 A1 US 6446729 B1	05-02-2002 30-04-2001 28-08-2002 18-06-2002 26-04-2001 10-09-2002
GB 2369382	A	29-05-2002	US 2002053439 A1 US 2002125008 A1 US 2002125009 A1	09-05-2002 12-09-2002 12-09-2002
WO 0206593	A	24-01-2002	AU 7343601 A WO 0206593 A1	30-01-2002 24-01-2002